

UWB Peel & Stick Appliqué Antenna, 3000 – 10000 MHz



Features

- O 3000 10000 MHz operational bandwidth
- O Low visibility from outside vehicle
- Ideal for mounting on non-metallic, low-loss materials such as glass, fiberglass, polyethylene, polycarbonate, and other plastics
- O Easily adheres to surface
- O Quick installation (< 1 minute)
- Highly efficient antenna
- O Other connector options available


Characteristics


| Model Number | AA-3000-10000 |
|-------------------|------------------|
| Frequency | 3000 – 10000 MHz |
| | 0.8 dBi @ 3 GHz |
| Gain | 3.4 dBi @ 6 GHz |
| | 3.1 dBi @ 9 GHz |
| Pattern | Near omni |
| Polarization | Vertical |
| VSWR | < 2.5:1 |
| Nominal Impedance | 50 Ohms |
| Size | 0.75" × 1.5" |
| Cable Length | 17.25" |
| Weight | 1 oz |
| Connector Type | SMA |


VSWR 6.0 5.5 5.0 4.5 4.0 3.5 3.0 2.5 2.0 1.5 1.0

Frequency (GHz)

Radiation Patterns







Radiation Patterns

octane is a division of Pharad, LLC. Octane is a registered trademark of Pharad, LLC. Specifications subject to change without notice.

1340 Charwood Road, Suite L · Hanover, MD 21076 · phone 410-590-3333 · email info@octanewireless.com www.octanewireless.com

Document Number: 900219